

DATA SHEET

| HART INTELLIGENT DIFFERENTIAL PRESSURE TRANSMITTER | |
|---|-----------------------------------|
| | |
| [LD301D] - HART INTELLIGENT DIFFERENTIAL PRESSURE TRANSMITTER | |
| LD301D-31I-B000-010 . A0/D0/G0/H0/I1/M0/P0/S0/Y0/J0 | |
| EQUIPMENT FEATURES | |
| [3] RANGE | 8.33 TO 1000 INH2O |
| [1] DIAPHRAGM MATERIAL AND FILL FLUID | 316L SST - SILICONE OIL |
| [I] FLANGES, ADAPTERS AND DRAIN/VENT VALVES MATERIAL | CF 8M / 316 SST |
| [B] WETTED O-RINGS MATERIAL | BUNA N |
| [0] DRAIN/VENT POSITION | WITHOUT DRAIN/VENT |
| [0] LOCAL INDICATOR | WITHOUT DIGITAL INDICATOR |
| [0] PROCESS CONNECTION | 1/4 - 18 NPT (WITHOUT ADAPTER) |
| [0] ELECTRICAL CONNECTION | 1/2 - 14 NPT |
| [1] WITH LOCAL ADJUSTMENT | WITH LOCAL ADJUSTMENT |
| [0] MOUNTING BRACKET | WITHOUT BRACKET |
| OTHER FEATURES | |
| [A0] FLANGES BOLTS AND NUTS MATERIAL | IN CARBON STEEL PLATED |
| [D0] FLANGE TYPE | SMAR STANDARD |
| [G0] OUTPUT SIGNAL | 4 - 20 MA |
| [H0] HOUSING MATERIAL | ALUMINIUM (IP/TYPE) |
| [I1] IDENTIFICATION PLATE | FM: XP, IS, NI, DI |
| [M0] MEMORY CONFIGURATION | WITH PID (AVAILABLE AND DISABLED) |
| [P0] PAINTING | GRAY MUNSELL N 6,5 |
| [S0] STANDARD FEATURES | SMAR |
| [Y0] DISPLAY UNIT | PERCENTAGE |
| [J0] TAG PLATE | WITH TAG |