




Axial-flow full cone nozzles

Series 490 / 491

NEW Patent pending





Non-clogging nozzle design. Stable spray angle. Particularly even liquid distribution.

Applications:
Cleaning and washing processes, surface spraying, Container cleaning, foam precipitation, degassing of liquids.



Series 490/491 represents a new generation within the axial-flow full cone nozzles product group. These nozzles were developed using state-of-the-art design and simulation methods (CFD).

Nozzles of series 490/491 replace series 460/461 which are still available on request.



Code	G	Dimensions [mm]			Hex/Flats	Weight Brass
		L ₁	L ₂	D		
CA	1/8 BSPT	18.0	6.5	10.0	11	13 g
CC	1/4 BSPT	22.0	10.0	13.0	14	18 g
CE	3/8 BSPT	24.5	10.0	16.0	17	30 g
CE	3/8 BSPT	30.0	10.0	16.0	17	50 g
CG	1/2 BSPT	32.5	13.0	21.0	22	60 g
CG	1/2 BSPT	43.5	13.0	21.0	22	85 g
AK	3/4 BSPP	42.0	15.0	32.0	27	190 g
AM	1 BSPP	56.0	17.0	40.0	36	350 g

Subject to technical modification.
In a critical installation situation, please ask for the exact dimensions.

Spray angle	Ordering no.										B Ø [mm]	E Ø [mm]	V̇ [l/min]								Spray diameter D at p=2 bar	
	Type	Mat. no.		Code									p [bar]								Diagram	
		1Y	30	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	1 BSPP									H=200 mm	H=500 mm			
										316L SS			Brass	0.5	1.0	2.0	3.0			5.0	7.0	10.0
45°	490.403	•	•	CA	-	-	-	-	-	-	1.25	1.25	0.57	0.78	1.00	1.18	1.44	1.65	1.90	160	400	
	490.523	•	•	CA	-	-	-	-	-	-	1.70	1.70	1.15	1.52	2.00	2.35	2.89	3.30	3.81	160	400	
	490.603	•	•	-	CC	CE*	-	-	-	-	2.00	2.00	1.81	2.39	3.15	3.70	4.54	5.20	6.00	160	400	
	490.643	•	•	-	-	CE*	-	-	-	-	2.45	2.45	2.30	3.03	4.00	4.70	5.77	6.60	7.61	160	400	
	490.683	-	•	-	-	CE*	-	-	-	-	2.55	2.55	2.67	3.79	5.00	5.88	7.21	8.25	9.52	160	400	
	490.703	-	•	-	-	CE*	-	-	-	-	2.65	2.65	3.22	4.24	5.60	6.59	8.08	9.24	10.66	160	400	
	490.723	-	•	-	-	CE*	-	-	-	-	2.85	2.85	3.62	4.77	6.30	7.41	9.09	10.40	11.99	160	400	
	490.783	-	•	-	-	-	CG	-	-	-	3.45	3.45	5.17	6.62	9.00	10.58	12.98	14.85	17.12	160	400	
	490.843	-	•	-	-	-	CG	-	-	-	3.80	3.80	7.18	9.47	12.50	14.70	18.03	20.63	23.80	160	400	
	60°	490.404	•	•	CA	-	-	-	-	-	-	1.15	1.15	0.57	0.78	1.00	1.18	1.44	1.65	1.90	220	560
490.444		•	•	CA	-	-	-	-	-	-	1.25	1.25	0.72	0.95	1.25	1.47	1.80	2.08	2.38	220	560	
490.484		•	•	CA	-	-	-	-	-	-	1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	220	560	
490.524		•	•	CA	-	-	-	-	-	-	1.60	1.60	1.15	1.52	2.00	2.35	2.89	3.30	3.81	220	560	
490.564		•	•	CA	-	-	-	-	-	-	1.80	1.80	1.44	1.89	2.50	2.94	3.61	4.13	4.78	220	560	
490.604		•	•	CA	CC	CE	-	-	-	-	2.05	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	220	560	
490.644		•	•	-	CC	CE	-	-	-	-	2.30	2.30	2.30	3.03	4.00	4.70	5.77	6.60	7.61	220	560	
490.684		•	•	-	CC	CE	-	-	-	-	2.60	2.60	2.67	3.79	5.00	5.88	7.21	8.25	9.52	220	560	
490.724		•	•	-	CC	CE	-	-	-	-	2.95	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	220	560	
490.764		•	•	-	-	CE	-	-	-	-	3.25	3.25	4.59	6.06	8.00	9.41	11.54	13.20	15.22	220	560	
490.804		•	•	-	-	CE	-	-	-	-	3.70	3.70	5.74	7.58	10.00	11.76	14.43	16.51	19.04	220	560	
490.844		•	•	-	-	-	CG	-	-	-	4.05	4.05	7.18	9.47	12.50	14.70	18.03	20.63	23.80	220	560	
490.884		•	•	-	-	-	CG	-	-	-	4.65	4.65	9.19	12.13	16.00	18.82	23.08	26.41	30.46	220	560	
490.924		•	•	-	-	-	-	AK	-	-	5.20	5.20	11.49	15.16	20.00	23.52	28.85	33.01	38.07	220	560	
490.964		•	•	-	-	-	-	AK	-	-	5.80	5.80	14.38	18.95	25.00	29.40	36.07	41.26	47.59	220	560	
491.044		•	•	-	-	-	-	AM	-	-	7.25	7.25	22.97	30.31	40.00	47.04	57.71	66.02	76.15	220	560	
491.084		•	•	-	-	-	-	AM	-	-	8.15	8.15	28.72	37.89	50.00	58.80	72.14	82.53	95.18	220	560	

* Only available in material 30 · B = bore diameter · E = narrowest free cross section

Continued on next page.


Conversion formula for the above series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{P_2}{P_1}\right)^{0.4}$



Axial-flow full cone nozzles

Series 490 / 491

NEW Patent pending



Spray angle	Type	Ordering no.								B Ø (mm)	E Ø (mm)	V [l/min]							Spray diameter D at p=2 bar	
		Mat. no.		Code								p [bar]								
		1Y	30																	
		316L SS	Brass	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	1 BSPP			0.5	1.0	2.0	3.0	5.0	7.0	10.0	H=200 mm	H=500 mm
90°	490.406	•	•	CA	-	-	-	-	-	1.20	1.20	0.57	0.76	1.00	1.18	1.44	1.65	1.90	380	860
	490.446	•	•	CA	-	-	-	-	-	1.30	1.30	0.72	0.95	1.25	1.47	1.80	2.06	2.38	380	860
	490.486	•	•	CA	-	-	-	-	-	1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	380	860
	490.526	•	•	CA	-	-	-	-	-	1.70	1.55	1.15	1.52	2.00	2.35	2.89	3.30	3.61	380	860
	490.566	•	•	CA	-	-	-	-	-	1.90	1.90	1.44	1.89	2.50	2.94	3.61	4.13	4.76	380	860
	490.606	•	•	CA	-	CE	-	-	-	2.10	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	380	860
	490.646	•	•	-	CC	CE	-	-	-	2.40	2.40	2.30	3.03	4.00	4.70	5.77	6.60	7.61	380	960
	490.686	•	•	-	CC	CE	-	-	-	2.70	2.70	2.87	3.79	5.00	5.86	7.21	8.25	9.52	380	960
	490.726	•	•	-	CC	CE	-	-	-	3.20	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	380	960
	490.746	•	•	-	-	CE	-	-	-	3.15	3.15	4.05	5.36	7.10	8.35	10.24	11.72	13.52	380	960
	490.766	•	•	-	-	CE	-	-	-	3.40	3.40	4.59	6.06	8.00	9.41	11.54	13.20	15.22	380	960
	490.806	•	•	-	-	CE	-	-	-	3.90	3.90	5.74	7.56	10.00	11.76	14.43	16.51	19.04	380	960
	490.846	•	•	-	-	CE	-	-	-	4.65	4.00	7.18	9.47	12.50	14.70	18.03	20.63	23.80	380	960
	490.886	•	•	-	-	-	CG	-	-	5.45	4.50	9.19	12.13	16.00	18.82	23.08	26.41	30.46	380	960
	490.926	•	•	-	-	-	CG	-	-	5.90	4.50	11.49	15.16	20.00	23.52	28.85	33.01	38.07	380	960
	490.966	•	•	-	-	-	CG	AK	-	6.55	4.85	14.36	18.96	25.00	29.40	36.07	41.26	47.59	380	960
	491.006	•	•	-	-	-	-	AK	-	7.55	5.50	18.09	23.87	31.50	37.05	45.45	51.99	59.97	380	960
	491.046	•	•	-	-	-	-	AK	-	8.60	6.60	22.97	30.31	40.00	47.04	57.71	66.02	76.15	380	960
	491.086	•	•	-	-	-	-	-	AM	9.45	7.25	28.72	37.89	50.00	58.80	72.14	82.53	95.18	380	960
	491.126	•	•	-	-	-	-	-	AM	10.40	8.00	36.16	47.75	63.00	74.09	90.89	103.95	119.93	380	960
491.146	•	•	-	-	-	-	-	AM	11.00	7.50	40.76	53.81	71.00	83.50	102.43	117.19	135.16	380	960	
120°	490.368	•	•	CA	-	-	-	-	-	0.85	0.85	0.36	0.46	0.63	0.74	0.91	1.04	1.20	680	1220
	490.408	•	•	CA	-	-	-	-	-	1.20	1.20	0.57	0.76	1.00	1.16	1.44	1.65	1.90	680	1220
	490.448	•	•	CA	-	-	-	-	-	1.30	1.30	0.72	0.95	1.25	1.47	1.80	2.06	2.38	680	1220
	490.488	•	•	CA	-	-	-	-	-	1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	680	1220
	490.528	•	•	CA	-	-	-	-	-	1.70	1.70	1.15	1.52	2.00	2.35	2.89	3.30	3.61	680	1220
	490.568	•	•	CA	-	-	-	-	-	1.90	1.90	1.44	1.89	2.50	2.94	3.61	4.13	4.76	680	1220
	490.608	•	•	CA	-	-	-	-	-	2.10	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	680	1220
	490.648	•	•	-	CC	CE	-	-	-	2.40	2.40	2.30	3.03	4.00	4.70	5.77	6.60	7.61	680	1330
	490.688	•	•	-	CC	CE	-	-	-	2.75	2.75	2.87	3.79	5.00	5.86	7.21	8.25	9.52	680	1330
	490.728	•	•	-	CC	CE	-	-	-	3.20	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	680	1330
	490.748	•	•	-	-	CE	-	-	-	3.20	3.20	4.05	5.36	7.10	8.35	10.24	11.72	13.52	680	1330
	490.768	•	•	-	-	CE	-	-	-	3.45	3.45	4.59	6.44	8.00	9.41	11.54	13.20	15.22	680	1330
	490.808	•	•	-	-	CE	-	-	-	3.90	3.90	5.74	7.56	10.00	11.76	14.43	16.51	19.04	680	1330
	490.848	•	•	-	-	CE	-	-	-	4.70	4.00	7.18	9.47	12.50	14.70	18.03	20.63	23.80	680	1330
	490.888	•	•	-	-	-	CG	-	-	5.10	4.50	9.19	12.13	16.00	18.82	23.08	26.41	30.46	680	1330
	490.928	•	•	-	-	-	CG	-	-	5.90	4.75	11.49	15.16	20.00	23.52	28.85	33.01	38.07	680	1330
	490.968	•	•	-	-	-	CG	AK	-	6.65	4.85	14.36	18.96	25.00	29.40	36.07	41.26	47.59	680	1330
	491.048	•	•	-	-	-	-	AK	-	9.20	5.85	22.97	30.31	40.00	47.04	57.71	66.02	76.15	680	1330
	491.128	•	•	-	-	-	-	-	AM	10.80	7.75	36.16	47.75	63.00	74.09	90.89	103.95	119.93	680	1330
	491.148	•	•	-	-	-	-	-	AM	11.40	7.65	40.76	53.81	71.00	83.50	102.43	117.19	135.16	680	1330

B = bore diameter · E = narrowest free cross section

Other nozzle materials (special alloys, plastics) are available on request.

Example Type + Material no. + Code = Ordering no.
for ordering: 490.406 + 1Y + CA = 490.406.1Y.CA