

Part Number 203602

Issue 1

1500 Series

1506M **C** **3** **G** **1** **B** **B**
 Model Design Shaft Adapter Housing Cover Rotation
 (GPM / 2000 RPM)

MODEL

1500M

GPM/2000 rpm

06 - 0.738 cir (12.10 cir)

10 - 1.180 cir (19.84 cir)

12 - 1.467 cir (24.19 cir)

15 - 1.771 cir (29.02 cir)

DESIGN

A- No outboard bearing

C- With shielded outboard bearing

SHAFTS

1. SAE "A" spline 5/8" Dia., 1.03 ext., use with adapters A & C only
2. 5/8" Dia. Short Key, 3/16" sq. key 7/8" long, 1.03 ext., use with adapters A & C only

3. 5/8" Dia. Long Key, 3/16" Sq. Key 1-1/4" long, 2.00 ext., use with adapters B, E & G only

4. 3/4" Dia. keyed, 3/16" Sq. Key 1-5/8" long, 2.50 ext., use with adapter D only

5. 5/8" Dia. threaded with Woodruff Key 1.78" ext., use with adapter E only

6. 3/4" Dia. keyed, 3/16" Sq. Key 1-5/8" long, 2.28 ext., use with adapters F & H only

ADAPTERS

- A.** 6 Bolt round, use with shafts 1 and 2 only
No outboard bearing
- B.** 6 Bolt round with outboard bearing, use with #3 shafts only
- C.** SAE "A" 2 Bolt with 5/8" shaft use with shafts 1 & 2 only
No outboard bearing

D. SAE "A" 2 Bolt with 3/4" shaft, use with #4 shaft only

E. SAE "A" 2 Bolt 5/8" shaft with outboard bearing, use with shafts 3 and 5 only

F. SAE "A" 2 Bolt with out board bearing 3/4" shaft, use with #6 shaft only

G. Foot mount, 5/8" shaft with outboard bearing, use with #3 shaft only

H. Foot mount, 3/4" shaft with outboard bearing, use with #6 shaft only

HOUSINGS

1. No Ports (Do not use with Cover A)
2. ANPT Pipe 1512 (1/2") only 1515 (3/4") only

3. Straight Threads 7/8" 1512 and 1515 only

4. Straight Threads 1-1/16", 1515 only

COVERS

A. No Ports (Do not use with #1 Housing)

B. 3/4" ANPT both ports (rear)

C. 7/8" Straight Thread both ports (rear)

D. 1-1/16" Straight Thread both ports (rear)

E. 7/8" Straight Thread both ports (side)

F. 1/2" ANPT both ports (side)

G. 3/4" ANPT both ports (side)

ROTATION

B. Bi-rotational