



POLYURETHANE TIMING BELTS

ARC-POWER SELF-TRACKING-SERIES

BAT10




STEEL Tension Member — standard
KEVLAR® Tension Member — optional



For more technical information
 please see catalog
B217 “ARC-POWER® TECHNOLOGY”

Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR
- T-Cover



OPEN ENDED – M




Pulleys
 page 168

Widths: Standard Belt Widths in mm:
 25 32 50 75 100

Lengths: Any length available – Stock Rolls: 50 meters

Ordering example: BRECO Timing Belt **75** **BAT10** / **4500** **M**


Belt Width _____
 Pitch _____
 Length _____
 Open Ended Length Code M _____



For more technical information
 please see catalog
B217 “ARC-POWER® TECHNOLOGY”

Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR
- T-Cover



SPliced AND WELDED ENDLESS – V



Pulleys
 page 168

Widths: Standard Belt Widths in mm:
 25 32 50 75 100

Lengths: Minimum Joined Length: 880 mm
 Length of timing belt can be specified in one tooth increments

Ordering example: BRECO Timing Belt **75** **BAT10** / **4500** **V**

Belt Width _____
 Pitch _____
 Length _____
 Joined Length Code V _____